

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it



## Technical Datasheet

### **tasker® C6015 – 6x0,15 mm<sup>2</sup>**

### **Braided Shielded Tinned Cable**



**CATEGORY** Braided Conductor Shielded Cable (See Data Network Catalogue)  
**APPLICATIONS** Data transmission and Electronics

- A:** Grey Soft **PVC** Sheath.  
Outer cable diam. Ø 6,20 (±0,20) mm.
- B:** Braided Shielding O.F.C. Tinned Copper covering 85%
- C:** Cores Insulation with Soft **PVC**. Core color code with DIN 47100 Standards.  
Stranded with waste filler between conductors and wrapped with Mylar Tape.  
Diam. Ø 1,20 (±0,20) mm.
- D:** Stranded O.F.C. Tinned Copper formation 19x0,10 mm.  
Nom. Cross section 6x0,15 mm<sup>2</sup>

**MARKING** **tasker®** C6015 6x0,15 - 25 AWG Professional Data Transmission Shielded Cable - Made in Italy

**CUSTOM PRODUCTION** This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**, or Metallic Armored.

#### Cable Properties

<b>Conductor Resistance</b>	118 Ω/Km
<b>Capacity Core/Core</b>	120 pF/m
<b>Capacity Core/Shield</b>	220 pF/m
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS3 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. B / 26.05.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			