

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it

## Technical Datasheet

# tasker® C800 - 2x0,22 mm<sup>2</sup>

### Digital Audio 110 Ohm Cable AES/EBU



**CATEGORY** Digital Audio Cable (See Audio Catalogue)  
**APPLICATIONS** Digital Audio Applications and DMX

- A:** Black soft PVC sheath. Outer cable Diam. Ø 4,40 (±0,10) mm.
- B:** Shielding O.F.C. Red Copper Spiral covering 100%  
+ O.F.C. tinned copper Drain Wire.
- C:** Core Insulation with PPE, colored one Red and one Blue.  
The conductors are wrapped together with waste textile filler.  
Diam. Ø 1,50 (±0,10) mm.
- D:** O.F.C. tinned copper formation 28x0,10 mm.  
Nom. Cross section 2x0,22 mm<sup>2</sup>

**MARKING** tasker® C800 2x0,22 mm<sup>2</sup> AES/EBU 110 Ω DIGITAL MULTILINE AUDIO CABLE -  
Made in Italy

**CUSTOM PRODUCTION** This product may be custom produced also in L.S.Z.H. polymer, PE, PUR,  
with or without Metallic Armor.

#### Cable Properties

<b>Conductor Resistance</b>	79,15 Ω/Km
<b>Capacity Core/Core</b>	50 pF/m
<b>Capacity Core/Shield</b>	95 pF/m
<b>Impedance</b>	110 Ω
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	X	Indoor	Interno Edificio	<b>INSTALLATION</b>	X	Fixed	Fissa	<b>INFORMATION</b>	X	RoHS3 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	X	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	X	Ver. B / 16.05.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			