

EF-W24


- Internally or externally fitted
- Covers 2.4GHz
- Simple & quick installation

The EF-W24 'easy fit' antenna is efficient & compact.

With a secure but easy to fit adhesive pad mounting, the EF-W24 antenna provides a huge range of possibilities for the installer.

Whether mounted by the windscreen pillar or behind the rear view mirror the only thing the user will notice is the superb quality of their data connection.

Technical Drawing EF-W24 Shown



M2M & ISM Band Wireless LAN Easyfit Antenna EF-W24




			Product Data	
Part No.				
		EF-W24-2F	EF-W24-3RPSP	
Electrical Data				
Frequency Range (MHz)		2400-2485N	2400-2485MHz	
Operational Band		2.4GHz WLAN		
Bandwidth at 2:1 VSWR		10%		
Peak Gain: Isotropic		2dBi		
Compared to 1/4 wave		0dBi	0dBi	
Patter		Omni-directi	Omni-directional	
Polarisation		Vertical	Vertical	
Impedance		50Ω	50Ω	
Max input power (W)		10	10	
Mechanical Data				
Dimensions (mm)	Height	113 (4.5")		
	Width	19 (0.7")	19 (0.7")	
	Thickness	2.5 (0.1"	2.5 (0.1")	
Operating Temp (°C)		-40° / +80°C (-40° / +176°F)		
Material		TPE	TPE	
Colour		Black	Black	
Mounting Data				
Fixing		Adhesive p	Adhesive pad	
Material		Acrylic adhesiv	Acrylic adhesive pad	
Colour		Black	Black	
Cable Data				
Cable Type		RG174	RG174	
Thickness (mm)		2.8		
Length (m)		2m	3m	

SMA Plug

Termination

Rev. Pol. SMA Plug



*VSWR mounted on glass sheet with 3m (10') of RG174 cable

Typical H-Plane (2400MHz)

