

MILAN S.r.l. a socio unico

Head Office – Export department:  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it



## Technical Datasheet



# tasker® TSK1115 - 2x2,50 mm<sup>2</sup> - Shielded Speaker Cable



**CATEGORY** Shielded Speaker Cable (See Audio Catalogue)  
**APPLICATIONS** Professional Loudspeakers and premade cables

- A:** Black Soft Flame Retardant PVC.  
Outer cable Diam. Ø 9,20 (±0,20) mm.
- B:** Shielding in O.F.C. red copper braid, covering 85%.
- C:** The cores are stranded in a pair with waste filler between conductors and wrapped with not woven polyester based tape.  
Core Insulation with a compact PE, colored one Red and one Black  
Diam. Ø 3,30 (±0,20) mm.
- D:** O.F.C. red copper formation 80x0,20 mm.  
Nom. Cross section 2x2,50 mm<sup>2</sup>.

**MARKING** **tasker®** TSK1115 2x2,50 – 13 AWG O.F.C. Shielded Speaker Cable  
 FirestoP® - Italy

**CUSTOM PRODUCTION** This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

### Cable Properties

<b>Conductor Resistance</b>	6,41 Ω/Km
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-20/+70°C

<b>USE</b>	X	Indoor	Interno Edificio	<b>INSTALLATION</b>	X	Fixed	Fissa	<b>INFORMATION</b>	X	RoHS2 Compliant
<b>Impiego</b>	X	Outdoor Limited	Esterno Limitato	<b>Posa</b>	X	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			