

4-Port 3G-SDI Input Board VM7404


- The VM7404 4-Port 3G-SDI Input Board offers an easy way to route any 4 SDI video and audio sources to multiple displays when used in combination with an ATEN Modular Matrix Switch. This input board provides the capability to connect to SDI sources, including 3G-SDI, HD-SDI and SD-SDI, and supports high quality video resolutions up to 1080p @ 60 Hz. The VM7404 also supports separate analog stereo audio signals that can be routed independently. Furthermore, the board is based on a hot-swappable design, allowing the ATEN Modular Matrix Switch to remain on while the board is changed. Ideal for surveillance systems and numerous other broadcast-grade A/V applications, the VM7404 allows you to effectively centralize routing for all your 3G / HD / SD-SDI devices.



Features

- Connects up to 4 SDI inputs
- Supports SD-SDI, HD-SDI and 3G-SDI formats
- Hot-swappable design for easy integration of I/O boards
- Compatible with the VM1600 - mix and match modular I/O boards for optimal flexibility

Note: When the VM7404 is used in conjunction with output boards featuring scalers, the Seamless Switch™, scaler and video wall functions can be used.



Specifications

Function	VM7404
Video Input	
Interfaces	4 x BNC Female
Impedance	75 Ω
Video	
Supported Resolutions	PAL @ 50 fps and NTSC @ 59.94 fps 720p @ 25, 29.97, 30, 50, 59.94, 60 fps 1080i @ 50, 59.94, 60 fps 1080PsF @ 25, 29.97, 30 fps 1080p @ 23.98, 24, 25, 29.97, 30, 50, 59.94, 60 fps Sampling structure and pixel depth: 4:2:2 10/12-bit, 4:4:4 10/12-bit
Max. Data Rate	2.97 Gpbs
Max. Distance	100 m (3G-SDI); 150 m (HD-SDI); 300 m (SD-SDI)
SDI Formats	3G-SDI, SMPTE-259, 292, 424, 425 Level A & B-DL
Audio Inputs	
Interfaces	4 x Captive Screw Connectors, 5 pole * Audio signal type: stereo, balanced / unbalanced
Power	
Consumption	16.0 W
Environmental	
Operating Temperature	0° to 40° C
Storage Temperature	-20° to 60° C
Humidity	0 - 80% RH, Non-Condensing
Physical Properties	
Housing	Metal
Weight	0.60 kg
Dimensions (L x W x H)	35.20 x 24.28 x 2.28 cm

* Note:

Supported audio signal types: stereo, balanced, unbalanced.
 Balanced audio maximum input/output level: 0.5 Vrms (-6.02 dBV @ 600 ohm)
 Unbalanced audio maximum input/output level: 1 Vrms (0 dBV @ 600 ohm)

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com

Publish Date: 08/2016 V1.0



© Copyright 2016 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.